

SWP-HA 2K HDMI Sender

Technical Specifications

Interface	HDMI x1 for audio and video input Type C x1 for power supply, pairing, upgrading, and touch back channel control
Devices supported	Not limited to PCs and OSs, all devices with HDMI output are supported
Software installation free	No driver installation needed, no software needed The hardware implement audio and video data acquisition, encoding and transmission
Supported wireless receivers	All SnapShow receivers, including OneDesk, meetingSpace series
Video input resolution	1920x1080P60, 1920x1080P30, 1366x768P60, 1280x800P60, 1280x720P60, 1024x768P60, 800x600P60
Encoding resolution/frame rate	Up to 1920x1080 FPS30
Audio	44.1KHZ/48KHZ/16bit PCM, Stereo
Wireless connection	Insert button to connect automatically, run automatically, share with one click away Comes with WiFi, no PC WiFi needed
Wireless transmission protocol	IEEE 802.11ac/802.11n
Wireless transmission rate	Up to 867Mbps
Wireless transmission distance	Up to 30 meters of virtual distance
Wireless transmission frequency band	5G/2.4G
Wireless encryption protocol	WPA2-PSK
Connection time	< 13 seconds
Transmission delay	Less than 150ms average
Reverse control	Support touch 10point reverse control (only Win7/Win8.1/Win10 systems are supported)
Power/power consumption	5V/500mA, average power consumption 1.5W
Temperature range	Operation: +5C ~ + 40c; Storage: -20c ~ +60c
Humidity range	Storage: 0 ~ 90% relative humidity, no condensation Operation: 0 ~90% relative humidity, no condensation

