

6.5" Coaxial Ceiling Loudspeaker(6W-12W-25W-50W)

Features

- Built-in 100v/70v transformer
- In-ceiling type loudspeaker
- 6.5" +1.5" coaxial speaker unit
- Power output 6W, 12W, 25W & 50W @100V
- Built-in crossover for hi-fi use
- Line input: 100V, 70V or 8 Ω
- Metal grille, ABS baffle & ABS back cover
- Paint in white color
- Secure flush mount installation

Description

The T-208P is a ceiling speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers.

The built-in 6.5"+1.5" coaxial speaker driver is designed of wide frequency response 100-18kHz, and its various power output from 6W, 12W, 25W & 50W could meet different room size applications. The power taps is convenient to switch the input from 100V to 70V or 8 Ω , thus this speaker support both high impedance input and low impedance input use. The metal grille, ABS baffle and ABS back cover are painted in attractive white color. Its flush mount type makes the easy and secure installation.

It is ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

Specification

Model	T-208P
Power Taps @100V	6W, 12.5W, 25W, 50W
Power Taps @70V	3W, 6W, 12.5W, 25W, 50W
Transformer Impedance	Black: Com Red: 1.7KΩ/800Ω/ 400Ω/200Ω/100Ω
Input	70V/100V/8Ω
SPL(1W/1M)	90dB
Max. SPL (Rated W/1M)	107dB
Frequency Response (-10dB)	90-20KHz
Finish	Baffle: ABS, White Grille: Steel, White
Speaker Driver	6.5" x 1 1.5" x 1
Cutout Size	250mm
Dimensions	280 x 190mm
Weight	2.8Kg
Mounting	Flush-mount dog ears



Website: www.itc-pa.com.cn; Mail: info@itc-pa.com.cn



T-208P 6.5" Coaxial Ceiling Loudspeaker(6W-12W-25W-50W)

Appearance:



Direction Diagram:



Frequency Response:



Website: www.itc-pa.com.cn; Mail: info@itc-pa.com.cn