

AP Series

800watts

AP-28A PORTABLE SPEAKER DUAL WOOFERS





AP-28A is the new developed active plastic speaker series with an aesthetically pleasing design. This series can be paired with various styles and features of power amplifiers as well as multi connection choices with USB, SD, Bluetooth, FM radio, stereo Bluetooth pairing, DSP processor function etc. Applicable to large or medium concerts, stage monitoring, commercial performances, meetings and other occasions.

The plastic cabinets are molded by high-pressure injection molding machine with high-strength polypropylene raw materials. And the speakers are equipped with high-performance compression tweeter and high-power woofer that produce a stable frequency response and extremely high sound reduction after profession calibration.

Feature

• Speaker type : 2-way active speaker

• Woofer : (8" x 12") x 2, 1.8" voice coil

 $\bullet \quad \hbox{Compression Driver}: \ 1.75'' \ \hbox{voice coil}, 1'' \ \hbox{throat}$

• Frequency Response : 45Hz \sim 20kHz

• Max SPL: 124dB / 134dB(Peak)

• Amplifier : Class AB Amplifier

• Power RMS: 400W / 800W (MAX)

• Built-in DSP processor mode : DEFAULT, DANCE, SPEECH, EXT SUB

• Built-in Media player: USB / SD-Card support MP3, WMA files. FM Radio, Wireless audio streaming Bluetooth

Specifications

Model	AP-28A
Туре	2-way active speaker
Transducer	Titanium Driver: 1" throat, 1.75" voice coil / Woofer: (8" x 12") x 2, 1.8" voice coil
Frequency Response	45Hz ∼ 20kHz
Rated Power	400W / 800W (MAX)
Amplifier	Class AB Amplifier
Maximum SPL	124dB / 134dB(Peak)
Qty per container 20'/140'/140'HC	210 / 425 / 495
Built-in DSP Processor	DEFAULT, DANCE, SPEECH, EXT SUB
Media player	USB / SD-Card support MP3, WMA files. FM Radio, Wireless audio streaming Bluetooth
Connection	Mic Input : XLR or 1/4" Jack Line Input: XLR or 1/4" Jack, RCA line Output: XLR
Operating voltage	AC 220~240V, 50/60Hz
Dimensions (W x H x D)	440 x 330 x 700mm
Net Weight	23kg